

The mdframed package

Examples for framemethod=PSTricks

Marco Daniel

v1.0

November 13, 2011

In this document I collect various examples for `framemethod=PSTricks`. Some presented examples are more or less exorbitant.

Contents

1 Loading	1	Example 2 – hidden line + frame title	2
2 Examples	1	Example 3 – Dash Lines	3
Example 1 – very simple	2	Example 4 – Double Lines	3

1 Loading

In the preamble only the package `mdframed` with the option `framemethod=PSTricks` is loaded. All other modifications will be done by `\mdfdefinestyle` or `\mdfsetup`.

Note

Every `\global` inside the examples is necessary to work with the package `showexpl`.

2 Examples

All examples have the following settings:

```
\mdfsetup{skipabove=\topskip, skipbelow=\topskip}
\newrobustcmd\ExampleText{%
An \textit{inhomogeneous linear} differential equation
has the form
\begin{align}
L[v] &= f,
\end{align}
where  $L$  is a linear differential operator,  $v$  is
the dependent variable, and  $f$  is a given non-zero
function of the independent variables alone.
}
```

Example 1 – very simple

```
\global\mdfdefinestyle{exampledefault}{%
  \linecolor=red,\linewidth=3pt,%
  \leftmargin=1cm,\rightmargin=1cm
}
\begin{mdframed}[style=exampledefault,\roundcorner=5]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \tag{1}$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 2 – hidden line + frame title

```
\global\mdfapptodefinestyle{exampledefault}{%
  \topline=false,\rightline=false,\bottomline=false}
\begin{mdframed}[style=exampledefault,frametitle={Inhomogeneous linear}]
\ExampleText
\end{mdframed}
```

Inhomogeneous linear

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \tag{2}$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 3 – Dash Lines

```
\global\mdfdefinestyle{exampledefault}{%
  pstrickssetting={linestyle=dashed,,linecolor=red,linewidth=5pt}
\begin{mdframed}[style=exampledefault,]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (3)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.

Example 4 – Double Lines

```
\global\mdfdefinestyle{exampledefault}{%
  pstrickssetting={doubleline=true,doublesep=3pt,
  linecolor=red,linewidth=5pt}
\begin{mdframed}[style=exampledefault,]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (4)$$

where L is a linear differential operator, v is the dependent variable, and f is a given non-zero function of the independent variables alone.