

Axes, axes, axes

Andreas Böhmann Michael Ummels

v1.0b – 2011/11/14

Abstract

The fontaxes package simulates multiple independent font selection axes on top of certain single NFSS axes: *base family*, *figure style*, and *figure alignment* on top of *family*; *primary shape* and *secondary shape* on top of *shape*; and *math weight* and *math figure alignment* on top of *math version*.

Contents

1	Introduction	1
2	Usage	2
2.1	Shape	2
2.2	Figure version	2
2.3	Math version	3
2.4	Additional commands	3
3	Implementation	4
3.1	High-level author commands (Level 1)	4
3.1.1	Shape	4
3.1.2	Figure version	5
3.1.3	Math version	6
3.2	Low-level author commands (Level 2)	7
3.3	Internals (Layer 3)	7
3.4	Encoding	9
3.5	Decoding	11
3.6	Compatibility	12
3.7	Tools	13
3.8	Tests	14

1 Introduction

The introduction of the New Font Selection Scheme (NFSS) has greatly simplified the usage of \LaTeX with fonts different from the Computer Modern fonts originally

designed for T_EX. However, the NFSS has some limitations. In particular, it defines only one axis for the font shape, which caters for both the actual *shape* of the font (e.g. upright, italic or slanted) and the *case* of the font (e.g. upper-lower case and small-caps). For example, if the current font shape is italic, then selecting small capitals using `\scshape` or `\textsc` will revert to an upright shape, even if the font has italic small capitals.

The `fontaxes` package alleviates the deficiencies of the NFSS by simulating multiple axes on top of single NFSS axes. In particular, it replaces the single NFSS shape axis by a primary and a secondary shape axis, catering for the shape and the case of the font, respectively. Moreover, the package introduces three new axes to deal with different *figure versions*, which are provided by many professional fonts.

2 Usage

You can load this package by adding

```
\usepackage{fontaxes}
```

to the preamble of your document. This redefines and makes available certain font selection commands, which are described in the rest of this section.

2.1 Shape

The `fontaxes` package splits the NFSS's single shape axis into two: the primary shape axis (n, it, etc.) and the secondary shape axis (ulc, sc, etc.).

`\upshape` The commands `\upshape`, `\itshape`, and `\slshape` are redefined to access the primary axis only. For access to a swash shape, the command `\swshape` has been added.

`\swshape` The commands `\scshape` and `\sscshape` (spaced small caps) access the secondary axis. To return from any small-caps shape to upper-lower case, you can use the command `\ulcshape`.

`\ulcshape` All these commands update the two shape axes using the low-level commands `\fontprimaryshape{<value>}` and `\fontsecondaryshape{<value>}`.

`\sscshape` If you want to change which values are used by the various commands `\<abbr>shape`, redefine the corresponding `\<abbr>default`. The additional commands `\swdefault`, `\sscdefault`, and `\ulcdefault` are provided with their default values `sw`, `ssc`, and `ulc`, respectively.

`\fontprimaryshape`
`\fontsecondaryshape`
`\swdefault`
`\sscdefault`
`\ulcdefault`

2.2 Figure version

Different figure versions are usually implemented as different font families (e.g. MinionPro-`{OsF, LF, T0sF, TLF}` or `ppl{j, x}`). The `fontaxes` package splits off the axes *figure style* and *figure alignment*, which leaves the *base family* (e.g. MinionPro or `ppl`).

<code>\txfigures</code> <code>\lnfigures</code> <code>\tbfigures</code> <code>\prfigures</code> <code>\fontfigurestyle</code> <code>\fontfigurealignment</code> <code>\fontbasefamily</code>	<p>The fontaxes package knows two figure styles, text and lining (accessible via <code>\txfigures</code> and <code>\lnfigures</code>), and two modes of figure alignment, tabular and proportional (accessible via the switches <code>\tbfigures</code> and <code>\prfigures</code>).</p> <p>Additionally, you can access both axes directly using the low-level commands <code>\fontfigurestyle{<value>}</code> and <code>\fontfigurealignment{<value>}</code>.</p> <p>If you want to change the font family without changing the figure version, use <code>\fontbasefamily{<value>}</code>. (All these commands require a successive <code>\selectfont</code> to make the changes take effect.)</p> <p>For choosing the figure versions to be used in math mode, you can use the corresponding axis <i>math figure alignment</i>. Note that there is currently no means for changing the figure style used in math.</p>
--	---

2.3 Math version

<code>\boldmath</code> <code>\unboldmath</code> <code>\tabularmath</code> <code>\proportionalmath</code> <code>\mathweight</code> <code>\mathfigurealignment</code>	<p>By default, \TeX provides two math versions, normal and bold, as well as commands <code>\boldmath</code> and <code>\unboldmath</code> for switching between them. The fontaxes packages redefines these commands to operate on the axis <i>math weight</i>.</p> <p>A second axis <i>math figure alignment</i> is introduced that allows you to switch between tabular and proportional figures using <code>\tabularmath</code> and <code>\proportionalmath</code>. (This assumes the presence of additional math versions tabular and boldtabular; the package will copy the setups of math versions normal and bold at the end of the preamble in case you do not provide your own declarations.)</p> <p>You can directly assign values to the axes using the low-level commands <code>\mathweight{<value>}</code> and <code>\mathfigurealignment{<value>}</code>.</p> <p>Table 1 summarizes which commands set which values on which axes.</p>
--	--

2.4 Additional commands

<code>\textsw</code> <code>\textssc</code> <code>\textulc</code> <code>\textfigures</code> <code>\liningfigures</code> <code>\tabularfigures</code> <code>\proportionalfigures</code> <code>\figureversion</code>	<p>Similar to the well-known <code>\textit</code>, <code>\textsc</code>, etc. this package provides commands <code>\textsw</code>, <code>\textssc</code>, <code>\textulc</code>, <code>\textfigures</code>, <code>\liningfigures</code>, <code>\tabularfigures</code> and <code>\proportionalfigures</code> that take one argument and apply the font change only to the argument. For example, <code>\textsw{<text>}</code> is roughly equivalent to <code>{\swshape<text>}</code> (but automatically adds italic corrections).</p> <p>The command <code>\figureversion{<options>}</code> allows easy switching of multiple aspects of figures simultaneously. It takes as an argument a comma-separated list of one or more of the following options:</p> <table border="0" style="margin-left: 40px;"> <tr> <td><code>text, osf</code></td> <td>for text figures,</td> </tr> <tr> <td><code>lining, lf</code></td> <td>for lining figures,</td> </tr> <tr> <td><code>tabular, tab</code></td> <td>for tabular figures,</td> </tr> <tr> <td><code>proportional, prop</code></td> <td>for proportional figures.</td> </tr> </table>	<code>text, osf</code>	for text figures,	<code>lining, lf</code>	for lining figures,	<code>tabular, tab</code>	for tabular figures,	<code>proportional, prop</code>	for proportional figures.
<code>text, osf</code>	for text figures,								
<code>lining, lf</code>	for lining figures,								
<code>tabular, tab</code>	for tabular figures,								
<code>proportional, prop</code>	for proportional figures.								

For example, `\figureversion{lf, tab}` selects tabular lining figures.

Table 1: Summary of commands

Command	Axis	Value	Default
<code>\upshape</code>	<code>\fontprimaryshape</code>	<code>\updefault</code>	n
<code>\itshape</code>		<code>\itdefault</code>	it
<code>\slshape</code>		<code>\sldefault</code>	sl
<code>\swshape</code>		<code>\swdefault</code>	sw
<code>\ulcshape</code>	<code>\fontsecondaryshape</code>	<code>\ulcdefault</code>	ulc
<code>\scshape</code>		<code>\scdefault</code>	sc
<code>\sscshape</code>		<code>\sscdefault</code>	ssc
<code>\txfigures</code>	<code>\fontfigurestyle</code>	text	
<code>\lnfigures</code>		lining	
<code>\tbfigures</code>	<code>\fontfigurealignment</code>	tabular	
<code>\prfigures</code>		proportional	
<code>\langle none \rangle</code>	<code>\fontbasefamily</code>	<i>\langle font-dependent \rangle</i>	
<code>\boldmath</code>	<code>\mathweight</code>	bold	
<code>\unboldmath</code>		normal	
<code>\tabularmath</code>	<code>\mathfigurealignment</code>	tabular	
<code>\proportionalmath</code>		proportional	

3 Implementation

3.1 High-level author commands (Level 1)

3.1.1 Shape

```

\upshape Axis 1: primary shape
\itshape 1 \*package)
\slshape 2 \DeclareRobustCommand\upshape{\not@math@alphabet\upshape\relax
\swshape 3 \fontprimaryshape\updefault\selectfont}
          4 \DeclareRobustCommand\itshape{\not@math@alphabet\itshape\mathit
          5 \fontprimaryshape\itdefault\selectfont}
          6 \DeclareRobustCommand\slshape{\not@math@alphabet\slshape\relax
          7 \fontprimaryshape\sldefault\selectfont}
          8 \DeclareRobustCommand\swshape{\not@math@alphabet\swshape\relax
          9 \fontprimaryshape\swdefault\selectfont}

\scshape Axis 2: secondary shape
\sscshape 10 \DeclareRobustCommand\scshape{\not@math@alphabet\scshape\relax
\ulcshape 11 \fontsecondaryshape\scdefault\selectfont}
          12 \DeclareRobustCommand\sscshape{\not@math@alphabet\sscshape\relax
          13 \fontsecondaryshape\sscdefault\selectfont}
          14 \DeclareRobustCommand\ulcshape{\not@math@alphabet\ulcshape\relax
          15 \fontsecondaryshape\ulcdefault\selectfont}

```

`\noscshape` Provide an alias for compatibility with the `slantsc` package.

```
16 \let\noscshape\ulcshape
```

`\swdefault`

`\ulcdefault` 17 `\providecommand\swdefault{sw}`

`\sscdefault` 18 `\providecommand\ulcdefault{ulc}`

```
19 \providecommand\sscdefault{ssc}
```

`\textsw`

`\textssc` 20 `\DeclareTextFontCommand{\textsw}{\swshape}`

`\textulc` 21 `\DeclareTextFontCommand{\textssc}{\sscshape}`

```
22 \DeclareTextFontCommand{\textulc}{\ulcshape}
```

3.1.2 Figure version

`\txfigures` Axis 1: figure style

`\lnfigures` 23 `\def\txfigures{\@nomath\txfigures`

```
24 \fontfigurestyle{text}\selectfont}
```

```
25 \def\lnfigures{\@nomath\lnfigures
```

```
26 \fontfigurestyle{lining}\selectfont}
```

`\tbfigures` Axis 2: figure alignment

`\prfigures` 27 `\def\tbfigures{\@nomath\tbfigures`

```
28 \fontfigurealignment{tabular}\selectfont}
```

```
29 \def\prfigures{\@nomath\prfigures
```

```
30 \fontfigurealignment{proportional}\selectfont}
```

`\figureversion` This code originally appeared in the package `MinionPro`. We have adapted it to work within `fontaxes`' framework and also changed some option names.

```
31 \newcommand\fontaxes@fv@prefix{fontaxes@fv@switch@}
```

```
32 \newcommand*\fontaxes@fv@newoption[1]{%
```

```
33 {\expandafter\newcommand\csname\fontaxes@fv@prefix #1\endcsname}
```

```
34 \fontaxes@fv@newoption{text}{\txfigures}
```

```
35 \fontaxes@fv@newoption{osf}{\txfigures}
```

```
36 \fontaxes@fv@newoption{lining}{\lnfigures}
```

```
37 \fontaxes@fv@newoption{lf}{\lnfigures}
```

```
38 \fontaxes@fv@newoption{tabular}{\tbfigures\tabularmath}
```

```
39 \fontaxes@fv@newoption{tab}{\tbfigures\tabularmath}
```

```
40 \fontaxes@fv@newoption{proportional}{\prfigures\proportionalmath}
```

```
41 \fontaxes@fv@newoption{prop}{\prfigures\proportionalmath}
```

We simply iterate over the list of figure versions specified in the argument to `\figureversion` and check if we have specified a matching option.

```
42 \newcommand\fontaxes@fv@list{}
```

```
43 \newcommand\fontaxes@fv{}
```

```
44 \DeclareRobustCommand*\figureversion[1]{%
```

```
45 \edef\fontaxes@fv@list{\zap@space#1 \@empty}%
```

```
46 \@for\fontaxes@fv:=\fontaxes@fv@list\do{%
```

```

47 \ifundefined{\fontaxes@fv@prefix\fontaxes@fv}{%
48   \PackageWarning{fontaxes}%
49   {Unknown figure style '\fontaxes@fv'\MessageBreak
50    specified as the argument to \string\figureversion.\MessageBreak
51    Figure style not changed}%
52 }{%
53   \@nameuse{\fontaxes@fv@prefix\fontaxes@fv}%
54 }%
55 }%
56 }

```

We have made `\figureversion` robust to protect it in moving arguments (e.g., section titles). Additionally, we want it to simply be ignored when `hyperref` is building PDF strings (e.g., for bookmarks). The same is true for similar commands, but we only include a selection of them (only the forms with arguments).

```

57 \AtBeginDocument{
58   \ifpackageloaded{hyperref}{%
59     \pdfstringdefDisableCommands{%
60       \let\figureversion\@gobble
61       \let\textfigures\@firstofone
62       \let\liningfigures\@firstofone
63       \let\tabularfigures\@firstofone
64       \let\proportionalfigures\@firstofone
65       \let\textsw\@firstofone
66       \let\textssc\@firstofone
67       \let\textulc\@firstofone
68     }%
69   }{}%
70 }

```

Axis 3: base family `\fontbasefamily{...}`

```

\textfigures
\liningfigures 71 \DeclareTextFontCommand{\textfigures}{\txfigures}
\tabularfigures 72 \DeclareTextFontCommand{\liningfigures}{\lnfigures}
\proportionalfigures 73 \DeclareTextFontCommand{\tabularfigures}{\tbfigures\tabularmath}
74 \DeclareTextFontCommand{\proportionalfigures}
75 {\prfigures\proportionalmath}

```

3.1.3 Math version

```

\boldmath Axis 1: weight
\unboldmath 76 \def\boldmath{\@nomath\boldmath
77   \mathweight{bold}}
78 \def\unboldmath{\@nomath\unboldmath
79   \mathweight{normal}}

```

```

\tabularmath Axis 2: figure alignment
\proportionalmath 80 \def\tabularmath{\@nomath\tabularmath

```

```

81 \mathfigurealignment{tabular}}
82 \def\proportionalmath{\@nomath\proportionalmath
83 \mathfigurealignment{proportional}}

```

3.2 Low-level author commands (Level 2)

```

\mathweight{bold,normal} sets \mathversion;
\mathfigurealignment{tabular,proportional} sets \mathversion;
\fontfigurestyle{text,lining} sets \fontfamily;
\fontfigurealignment{tabular,proportional} sets \fontfamily;
\fontbasefamily{...} sets \fontfamily;
\fontprimaryshape{n,it,sl,sw} sets \fontshape;
\fontsecondaryshape{ulc,sc,ssc} sets \fontshape.

```

```

\mathweight
\mathfigurealignment
84 \DeclareRobustCommand\mathweight[1]{%
85 \fontaxes@get@math \edef\fontaxes@math@weight{#1}\fontaxes@set@math}
86 \DeclareRobustCommand\mathfigurealignment[1]{%
87 \fontaxes@get@math \edef\fontaxes@math@align{#1}\fontaxes@set@math}

\fontfigurestyle
\fontfigurealignment
\fontbasefamily
88 \DeclareRobustCommand\fontfigurestyle[1]{%
89 \fontaxes@get@family \edef\fontaxes@figure@style{#1}\fontaxes@set@family}
90 \DeclareRobustCommand\fontfigurealignment[1]{%
91 \fontaxes@get@family \edef\fontaxes@figure@align{#1}\fontaxes@set@family}
92 \DeclareRobustCommand\fontbasefamily[1]{%
93 \fontaxes@get@family \edef\fontaxes@family@base{#1}\fontaxes@set@family}

\fontprimaryshape
\fontsecondaryshape
94 \DeclareRobustCommand\fontprimaryshape[1]{%
95 \fontaxes@get@shape \edef\fontaxes@shape@one{#1}\fontaxes@set@shape}
96 \DeclareRobustCommand\fontsecondaryshape[1]{%
97 \fontaxes@get@shape \edef\fontaxes@shape@two{#1}\fontaxes@set@shape}

```

3.3 Internals (Layer 3)

```

\fontaxes@set@math sets \mathversion;
\fontaxes@set@family sets \fontfamily;
\fontaxes@set@shape sets \fontshape.

```

```

\fontaxes@math@weight
\fontaxes@math@align
\fontaxes@family@base
\fontaxes@figure@style
\fontaxes@figure@align
\fontaxes@shape@one
\fontaxes@shape@two
The macros that hold the current values of the axes (here with some de-
fault values that will most certainly be overwritten during initialization; see
\fontaxes@get@...).
98 \newcommand*\fontaxes@math@weight{normal}
99 \newcommand*\fontaxes@math@align{proportional}
100 \newcommand*\fontaxes@family@base{cmr}
101 \newcommand*\fontaxes@figure@style{lining}

```

```

102 \newcommand*\fontaxes@figure@align{proportional}
103 \newcommand*\fontaxes@shape@one{n}
104 \newcommand*\fontaxes@shape@two{ulc}

\fontaxes@set@math
\fontaxes@set@family 105 \newcommand*\fontaxes@set@math{%
\fontaxes@set@shape 106 \fontaxes@encode@math
107 \mathversion{\fontaxes@code}%
108 \fontaxes@save\math@version}
109 \newcommand*\fontaxes@set@family{%
110 \fontaxes@encode@family
111 \fontfamily{\fontaxes@code}%
112 \fontaxes@save\f@family}
113 \newcommand*\fontaxes@set@shape{%
114 \fontaxes@encode@shape
115 \fontshape{\fontaxes@code}%
116 \fontaxes@save\f@shape}

\fontaxes@get@math Check for changes: if changed, try to decode and update axes.
\fontaxes@get@family 117 \newcommand*\fontaxes@get@math{%
\fontaxes@get@shape 118 \iffontaxes@changed\math@version{%
119 \fontaxes@decode@{math}{\math@version}%
120 \ifx\fontaxes@edoc\relax\else
121 \edef\fontaxes@math@weight{\expandafter\@firstoftwo\fontaxes@edoc}%
122 \edef\fontaxes@math@align{\expandafter\@secondoftwo\fontaxes@edoc}%
123 \fi
124 \fontaxes@save\math@version
125 }{}%
126 }

127 \newcommand*\fontaxes@get@family{%
128 \iffontaxes@changed\f@family{%
129 \let\fontaxes@edoc\relax
130 \expandafter\fontaxes@split@family\f@family--\@nnil
131 \ifx\fontaxes@split@suffix\relax\else
132 \fontaxes@decode@{figures}{\fontaxes@split@suffix}%
133 \fi
134 \ifx\fontaxes@edoc\relax

Try alternative.
135 \expandafter\fontaxes@split@familyalt\f@family
136 \@empty\@empty\@empty\@empty\@nnil
137 \ifx\fontaxes@split@suffix\relax\else
138 \fontaxes@decode@{figuresalt}{\fontaxes@split@suffix}%
139 \fi
140 \ifx\fontaxes@edoc\relax
141 \fontaxes@warn@undecodable{family '\f@family'}%
142 \edef\fontaxes@family@base{\f@family}%
143 \else
144 \edef\fontaxes@family@base{\fontaxes@split@prefix}%
145 \edef\fontaxes@figure@style{\expandafter\@firstoftwo\fontaxes@edoc}%

```


Do not overwrite align (does not occur in alternative naming scheme).

```

146     \fi
147   \else
Store values.
148     \edef\fontaxes@family@base{\fontaxes@split@prefix}%
149     \edef\fontaxes@figure@style{\expandafter\@firstoftwo\fontaxes@edoc}%
150     \edef\fontaxes@figure@align{\expandafter\@secondoftwo\fontaxes@edoc}%
151     \fi
152   }{}%
153 }

154 \newcommand*\fontaxes@get@shape{%
155   \iffontaxes@changed\fontaxes@shape{%
156     \fontaxes@decode@{shape}{\fontaxes@shape}%
157     \ifx\fontaxes@edoc\relax\else
158       \edef\fontaxes@shape@one{\expandafter\@firstoftwo\fontaxes@edoc}%
159       \edef\fontaxes@shape@two{\expandafter\@secondoftwo\fontaxes@edoc}%
160       \fi
161       \fontaxes@save\fontaxes@shape
162     }{}%
163   }

```

3.4 Encoding

```

\fontaxes@encode@math
\fontaxes@encode@family
\fontaxes@encode@figures
\fontaxes@encode@figuresalt
\fontaxes@encode@shape
164 \newcommand*\fontaxes@encode@math{%
165   \fontaxes@encode@{math}{\fontaxes@math@weight}{\fontaxes@math@align}}%
166 }
Default is concatenation.
167 \newcommand*\fontaxes@encode@math@default{%
168   \edef\fontaxes@code{\fontaxes@math@weight\fontaxes@math@align}}
169 \newcommand*\fontaxes@encode@family{%
170   \fontaxes@encode@{family}
171   {\fontaxes@family@base}{\fontaxes@figure@style}{\fontaxes@figure@align}}%
172 }
Try different naming conventions.
173 \newcommand*\fontaxes@encode@family@default{%
174   \fontaxes@encode@figures
175   \edef\fontaxes@code{\fontaxes@family@base-\fontaxes@code}%
176   \fontaxes@check@family\fontaxes@code
177   \iffontaxes@exists\else
178     \fontaxes@encode@figuresalt
179     \edef\fontaxes@code{\fontaxes@family@base\fontaxes@code}%
180     \fontaxes@check@family\fontaxes@code
181     \iffontaxes@exists\else
182       \edef\fontaxes@code{\fontaxes@family@base}%
183     \fi

```

```

184 \fi
185 }

186 \newcommand*\fontaxes@encode@figures{%
187   \fontaxes@encode@{figures}{\fontaxes@figure@style}\fontaxes@figure@align}%
188 }
189 \newcommand*\fontaxes@encode@figures@default{%
190   \edef\fontaxes@code{0sF}%
191   \PackageWarning{fontaxes}{Unknown figure version
192     '\fontaxes@figure@style\space + \fontaxes@figure@align'\MessageBreak
193     Encoding to '\fontaxes@code'}%
194 }

195 \newcommand*\fontaxes@encode@figuresalt{%
196   \fontaxes@encode@{figuresalt}{\fontaxes@figure@style}\fontaxes@figure@align}%
197 }
198 \newcommand*\fontaxes@encode@figuresalt@default{%
199   \PackageWarning{fontaxes}{Unknown figure version
200     '\fontaxes@figure@style\space + \fontaxes@figure@align'\MessageBreak
201     Encoding to '\fontaxes@code'}%
202   \edef\fontaxes@code{j}%
203 }

204 \newcommand*\fontaxes@encode@shape{%
205   \fontaxes@encode@{shape}{\fontaxes@shape@one}\fontaxes@shape@two}%
206 }

```

Default is (reverse) concatenation.

```

207 \newcommand*\fontaxes@encode@shape@default{%
208   \edef\fontaxes@code{\fontaxes@shape@two\fontaxes@shape@one}%
209 }

```

\fontaxes@encode@

```

210 \newcommand*\fontaxes@encode@[2]{%
211   \ifundefined{fontaxes@encode@#1#2}
212     {\@nameuse{fontaxes@encode@#1@default}}
213     {\edef\fontaxes@code{\@nameuse{fontaxes@encode@#1#2}}}%
214 }

```

\fontaxes@naming@exception To do: Add a user interface to specify naming exceptions.

```

215 \newcommand*\fontaxes@naming@exception[3]{%
216   \expandafter\edef\csname fontaxes@encode@#1#2\endcsname{#3}%
217 }

```

The following alias is defined for compatibility with package files generated by autoinst.

```

218 \let\fa@naming@exception\fontaxes@naming@exception

```

The defaults n and ulc disappear when combined.

```

219 \fontaxes@naming@exception{shape}{n}{ulc}{n}
220 \fontaxes@naming@exception{shape}{n}{sc}{sc}
221 \fontaxes@naming@exception{shape}{n}{ssc}{ssc}

```

```

222 \fontaxes@naming@exception{shape}{{it}{ulc}}{it}
223 \fontaxes@naming@exception{shape}{{sl}{ulc}}{sl}
224 \fontaxes@naming@exception{shape}{{sw}{ulc}}{sw}

```

The defaults disappear in the concatenation. `boldtabular` is formed regularly.

```

225 \fontaxes@naming@exception{math}{{normal}{proportional}}{normal}
226 \fontaxes@naming@exception{math}{{normal}{tabular}}{tabular}
227 \fontaxes@naming@exception{math}{{bold}{proportional}}{bold}

```

Provide abbreviations for font family suffixes.

```

228 \fontaxes@naming@exception{figures}{{text}{proportional}}{OsF}
229 \fontaxes@naming@exception{figures}{{text}{tabular}}{TOsF}
230 \fontaxes@naming@exception{figures}{{lining}{proportional}}{LF}
231 \fontaxes@naming@exception{figures}{{lining}{tabular}}{TLF}

```

The `j/x` naming convention does not know about different figure alignments; let us silently ignore these.

```

232 \fontaxes@naming@exception{figuresalt}{{text}{proportional}}{j}
233 \fontaxes@naming@exception{figuresalt}{{text}{tabular}}{j}
234 \fontaxes@naming@exception{figuresalt}{{lining}{proportional}}{x}
235 \fontaxes@naming@exception{figuresalt}{{lining}{tabular}}{x}

```

3.5 Decoding

Detect if `\mathversion`, `\fontshape`, `\fontfamily` have been used not under control of this package.

```

\fontaxes@figure@style@domain
\fontaxes@figure@align@domain
\fontaxes@shape@one@domain
\fontaxes@shape@two@domain
\fontaxes@math@weight@domain
\fontaxes@math@align@domain

```

Assuming an injective encoding function, we can construct decoding tables when we know the function's domain. To do: Warn if decoding entries are overwritten (if the function is not injective).

```

236 \newcommand*\fontaxes@figure@style@domain{text,lining}
237 \newcommand*\fontaxes@figure@align@domain{proportional,tabular}
238 \newcommand*\fontaxes@shape@one@domain{n,it,sl,sw}
239 \newcommand*\fontaxes@shape@two@domain{ulc,sc,ssc}
240 \newcommand*\fontaxes@math@weight@domain{normal,bold}
241 \newcommand*\fontaxes@math@align@domain{proportional,tabular}

```

```

\fontaxes@create@decode@table #1 name, #2 list of axes

```

```

242 \newcommand*\fontaxes@create@decode@table[2]{%
243   \begingroup
244   \fontaxes@foreach{#2}{%
245     \@nameuse{fontaxes@encode@#1}%
246     \global\expandafter
247     \edef\csname fontaxes@decode@#1{\fontaxes@code}\endcsname{#2}%
248   }%
249   \endgroup
250 }

```

```

251 \AtEndOfPackage{
252   \fontaxes@create@decode@table{figures}
253   {{\fontaxes@figure@style}{\fontaxes@figure@align}}
254   \fontaxes@create@decode@table{figuresalt}
255   {{\fontaxes@figure@style}{\fontaxes@figure@align}}
256   \fontaxes@create@decode@table{shape}
257   {{\fontaxes@shape@one}{\fontaxes@shape@two}}
258   \fontaxes@create@decode@table{math}
259   {{\fontaxes@math@weight}{\fontaxes@math@align}}
260 }

\fontaxes@warn@undecodable

261 \newcommand*\fontaxes@warn@undecodable[1]{%
262   \PackageWarning{fontaxes}{I don't know how to decode\MessageBreak #1}}

\fontaxes@decode@ Interpret the decoding tables.

263 \newcommand*\fontaxes@decode@[2]{%
264   \ifundefined{fontaxes@decode@#1{#2}}{%
265     \let\fontaxes@edoc\relax
266     \fontaxes@warn@undecodable{#1 '#2'}%
267   }\edef\fontaxes@edoc{\@nameuse{fontaxes@decode@#1{#2}}}%
268 }

\fontaxes@save Save states of macros for future comparison.
\iffontaxes@changed
269 \newcommand*\iffontaxes@changed[1]{%
270   \expandafter\ifx\csname fontaxes@last@\string#1\endcsname#1%
271     \expandafter\@secondoftwo
272   \else
273     \expandafter\@firstoftwo
274   \fi
275 }
276 \newcommand*\fontaxes@save[1]{%
277   \expandafter\let\csname fontaxes@last@\string#1\endcsname#1%
278 }

```

3.6 Compatibility

If no math versions `tabular` and `boldtabular` are defined in the preamble, we provide defaults by copying the states of normal and bold (assuming, in turn, that these two exist).

```

279 \AtBeginDocument{%
280   \fontaxes@provide@mv@copy{tabular}{normal}%
281   \fontaxes@provide@mv@copy{boldtabular}{bold}%
282 }

```

`\fontaxes@provide@mv@copy` Declare math version #1 to be a copy of math version #2 if #1 does not exist already. To accomplish this, we have to know that a math version's configuration is

basically stored in a macro `\mv@⟨name⟩` (which makes us dependent on the NFSS implementation; sigh ...).

```

283 \newcommand*\fontaxes@provide@mv@copy[2]{%
284   \@ifundefined{mv@#1}{%
285     \DeclareMathVersion{#1}%
286     \expandafter\let\csname mv@#1\expandafter\endcsname
287       \csname mv@#2\endcsname
288   }{}%
289 }

```

3.7 Tools

`\fontaxes@check@family` Check if family switching would yield an existing shape.

```

\iffontaxes@exists 290 \newif\iffontaxes@exists
291 \newcommand*\fontaxes@check@family[1]{%
292   \begingroup
293   \fontfamily{#1}\try@load@fontshape
294   \expandafter
295   \ifx\csname\curr@fontshape\endcsname\relax
296     \aftergroup\fontaxes@existsfalse
297   \else
298     \aftergroup\fontaxes@existstrue
299   \fi
300 \endgroup
301 }

```

`\fontaxes@split@prefix` The results of splitting a family name.

```

\fontaxes@split@suffix 302 \newcommand*\fontaxes@split@prefix{}
303 \newcommand*\fontaxes@split@suffix{}

```

`\fontaxes@split@family` Font name contains one hyphen; split there.

```

304 \newcommand*\fontaxes@split@family{}
305 \def\fontaxes@split@family#1-#2-#3\@nnil{%
306   \let\fontaxes@split@prefix\relax
307   \let\fontaxes@split@suffix\relax
308   \def\@tempa{#3}%
309   \ifx\@tempa\@empty\else
310     \def\fontaxes@split@suffix{#2}%
311     \ifx\fontaxes@split@suffix\@empty
312       \let\fontaxes@split@suffix\relax
313     \else
314       \def\fontaxes@split@prefix{#1}%
315     \fi
316   \fi
317 }

```

`\fontaxes@split@familyalt` Name consists of four characters; split off the last one. If there are just three characters, the default suffix is ‘x’.

```

318 \newcommand*\fontaxes@split@familyalt{}
319 \def\fontaxes@split@familyalt#1#2#3#4#5\@nnil{%
320   \let\fontaxes@split@prefix\relax
321   \let\fontaxes@split@suffix\relax
322   \edef\@tempa{#5}%
323   \ifx\@tempa\@empty
324     \ifx\@empty#4%
325       \def\fontaxes@split@prefix{#1#2#3}%
326       \def\fontaxes@split@suffix{x}%
327     \else
328       \def\fontaxes@split@prefix{#1#2#3}%
329       \def\fontaxes@split@suffix{#4}%
330     \fi
331   \fi
332 }

```

`\fontaxes@foreach` Execute #2 for each combination of values of the axes given in #1 (in the form `{\cs}{\cs}...`).

```

333 \newcommand\fontaxes@foreach[2]{%
334   \begingroup
335   \def\fontaxes@foreach@{#2}%
336   \@tfor\@tempa:=#1\do{%
337     \@temptokena\expandafter{\fontaxes@foreach@}%
338     \edef\fontaxes@foreach@{%
339       \noexpand\@for
340       \expandafter\noexpand\@tempa:=%
341       \expandafter\noexpand\csname
342         \expandafter\expandafter
343         \expandafter\@gobble
344         \expandafter\string\@tempa
345         @domain%
346       \endcsname
347       \noexpand\do{\the\@temptokena}%
348     }%
349   }%
350   \expandafter\endgroup\fontaxes@foreach@
351 }
352 \end{package}

```

3.8 Tests

The file `test-fontaxes.tex` (docstrip target test) exercises some features of `fontaxes`. Since it is rather ad-hoc code, it is not shown here. (It also requires the `MinionPro` package.)